



Figure 1: Lucid Loop system schematic. Painterly and Deep Dream creatively generate visuals to emulate dreams. The virtual environment becomes more lucid or “clear” when the participant’s physiological signals indicate increased awareness.

Lucid Loop: A Virtual Deep Learning Biofeedback System for Lucid Dreaming Practice

Alexandra Kitson, Steve DiPaola, Bernhard E. Riecke
 Simon Fraser University
 Surrey, BC, Canada
 akitson@sfu.ca, sdipaola@sfu.ca, ber1@sfu.ca

ABSTRACT

Lucid dreaming, knowing one is dreaming while dreaming, is an important tool for exploring consciousness and bringing awareness to different aspects of life. We present a proof-of-concept system called *Lucid Loop*: a virtual reality experience where one can practice lucid awareness via biofeedback. Visuals are creatively generated before your eyes using a deep learning Artificial Intelligence algorithm to emulate the unstable and ambiguous nature of dreams. The virtual environment becomes more lucid or “clear” when the participant’s physiological signals, including brain waves, respiration, and heart rate, indicate focused attention. *Lucid Loop* enables the virtual embodied experience of practicing lucid dreaming where written descriptions fail. It offers a valuable and novel technique for simulating lucid dreaming without having to be asleep. Future developments will validate the system and evaluate its ability to improve lucidity within the system by detecting and adapting to a participant’s awareness.

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

CHI’19 Extended Abstracts, May 4–9, 2019, Glasgow, Scotland Uk

© 2019 Copyright held by the owner/author(s).

ACM ISBN 978-1-4503-5971-9/19/05.

<https://doi.org/10.1145/3290607.3312952>

KEYWORDS

virtual reality; biofeedback; lucid dreaming; artificial intelligence; deep dream.

Table 1: EEG Frequency Band Interpretation [19]

Band	Range	State
Gamma γ	30-50Hz	hyperactive
Beta β	13-30Hz	alertness
Alpha α	8-13Hz	relaxation
Theta θ	4-8Hz	meditative
Delta δ	0.5-4Hz	deep sleep

INTRODUCTION

Lucid dreaming is being aware one is dreaming while in a dream, allowing the dreamer to take control and do anything they want [14]. Lucid dreaming can be the ultimate entertainment, but is also a space to solve problems, be creative, rehearse situations, and work through psychological issues [21, 23]. Yet, learning to lucid dream takes time and practice, and not everyone is convinced by, nor successful with, traditional training methods that primarily use written and audio dream guides. *Lucid Loop* is a virtual reality (VR) experience that uses biofeedback from brain waves, heart rate, and respiration to help participants practice lucid dreaming awareness. Participants will receive artful visual feedback based on Deep Convolutional Neural Networks (DCNNs) in a VR head mounted display (HMD).

To the best of the authors' knowledge, this is the first VR experience that uses biofeedback to generate artistic representations of lucid dreaming practices. The main scientific contribution is twofold: improving our understanding of lucid dreaming awareness and creating a design of a new tool for simulating lucid dreaming without having to be asleep. We are developing this tool, which we will test and iteratively refine through both quantitative and qualitative measures. The goal is to have the VR experience directly respond to participants' physiological states of awareness that closely map to states of lucid dreaming awareness in order to gain its many benefits.

RELATED WORK**Deep Convolutional Neural Networks and Art**

DCNNs are mainly used to classify images, objects, and faces [13], and their analysis requires innovative visualization methods. Google Researchers developed a novel visualization method called *Deep Dream*, whose goal is "to check what [the] network learned during training; [provide] a new way to remix visual concepts or perhaps even shed a little light on the roots of the creative process in general" [17]. This *Deep Dream* style essentially fuses the content from one image and the style from another into one novel image, resulting in an image with a dream-like quality (Figure 2). Researchers/Artists have begun to take advantage of this artistic quality to express visual creativity [5, 16].

Virtual Reality and Biofeedback for Awareness

In the context of lucid dreaming, awareness is defined here as the explicit recognition of one's current experience. The goal of lucid dreaming and similar practices, such as meditation and yoga, is increasing awareness. In doing so, we can understand ourselves and the world around us on a deeper level [9]. Thus, the practice of lucid dreaming itself is beneficial because it provides us an opportunity to question reality and become more aware of our surroundings and internal physiological state.

One way to practice awareness of our physiological states is through biofeedback, a training technique to help people learn how to change their physiological response patterns to improve their

mental and emotional state [8]. Neurofeedback is a specific type of biofeedback where participants respond to a display of their own brainwaves; specific bands of brainwaves have been correlated with different physiological states (see Table 1). To enhance the experiential qualities of biofeedback, several researchers have added VR—review [11]. For example, *PsychicVR* maps concentration to levitation and increased virtual fire to promote mindfulness [2]. *Pulse Breath Water* is a VR experience with affect estimation in sound to promote relaxation, calm, engagement, and breath awareness [20]. We use biofeedback and VR for the same reasons previous researchers have, with the addition that other methods of learning lucid dreaming awareness can be inaccessible and challenging, e.g., written guides, or more expensive and carry higher risks, e.g., transcranial alternating current stimulation [25].

Technology Mediated Experiences of Altered States

Altered states of consciousness can provide people with powerful and sometimes life-altering experiences. Technology can support these experiences in a more accessible way than others, such as psychedelics and religious ceremonies. Moreover, technologies like VR can amplify immersion and realism beyond other media, thus enhancing the experience and potential positive outcomes. Yet, many technologically mediated experiences of altered states, especially lucid dreaming, lack empirical studies to back their claims. *SoundSelf* [3] and *V.DREAM* [1] are VR experiences that use psychedelic-inspired lights and sounds to try to induce trance-like states. *Somnai* is a guided lucid dreaming-inspired mixed reality experience with intricate multisensory stimuli [6].

There exist a few research-based designs. One such experience is *Hallucination Machine*, which uses DCNNs and panoramic videos of natural scenes, viewed immersively through an HMD. *Hallucination Machine* was shown to phenomenologically induce an experience similar to psychedelics, although the temporal distortion commonly associated with altered states was not evoked [24]. However, this system only allows passive viewing from one perspective and does not enable interactivity that would help participants reach this altered state naturally. Interactivity is important here since lucid dreaming requires the dreamer to actively move from non-lucid awareness to lucid, whereas psychedelics automatically provides hallucinations without active participation.

LUCID LOOP

Our aim is to simulate the visual and auditory aspects of lucid dreaming using *Deep Dream* to produce an embodied experience where participants may practice lucid dreaming awareness via biofeedback and VR. Visuals and sounds will become clearer, or more lucid, as participants' increase their awareness, similar to actual lucid dreaming [7].

In *Lucid Loop*, the participant wears a *Muse 2* EEG that also detects heart rate and respiration, and an HMD, e.g., Oculus Quest, while experiencing a short, looping virtual experience generated by the *Deep Dream* algorithm (see Figure 1). 3D spatialized audio will be presented through headphones to



Figure 2: Unity scene (Asset Store: *Alpine Environment*) with *Deep Dream* (deepdreamgenerator.com) that makes different outputs depending on layer depth, from low (top) to high (bottom)

give the listener the impression of a realistic sound source within a 3D environment. *Muse 2* detects participant’s brainwaves that are correlated with certain states (Table 1). In *Lucid Loop*, participants are given positive visual and auditory feedback about their awareness when their physiology changes similarly to what is observed for lucid dreaming. That is, visuals and sound increase in clarity when EEG β and γ band powers increase, α and θ band powers decrease, and heart and respiration rate increase; vice-versa when visuals and sounds decrease. Lucid dreaming studies show elevated levels of autonomic nervous system activity occurs 30sec before the onset of a lucid dream, as evidenced through respiration rate, heart rate, and skin potential [15]. EEG studies show increased β band power over parietal regions and γ in frontal regions during lucid compared to baseline REM sleep [10, 26].

We chose to use artistic representations of data as opposed to graphical or more simplistic representations for two main reasons: one because understanding raw data for the average person is not intuitive; two because we wanted the experience itself to be intrinsically rewarding even if one is unsuccessful in trying to change their physiological state.

VR Visual Design

We use an HMD with six degrees-of-freedom head-tracking to enhance the immersive experiential qualities of lucid dreaming and allow the participant to look around naturally. *Hallucination Machine* used 360 panoramic video with *Deep Dream*, which can give a more realistic simulation [24]; however, we chose a computer graphics approach to allow real-time modification of any element, providing more flexibility for future iterations and control over experimental variables. *Lucid Loop* will be created in Unity, with visuals modified using *Deep Dream* and Painterly—a non-photorealistic rendering system that uses algorithmic, particle system and noise modules to generate artistic colour palettes, stroking and styles [4]. In *Lucid Loop*, we aim for a visual effect similar to lucid dreaming awareness, where bizarreness is needed for the dawning of dreaming awareness, but once achieved, the lucid dream scene is relatively realistic [7]. We are inspired by research on the phenomenology of lucid dreaming for introspection and VR [12], which suggests the use of nature, abstraction, clarity, curiosity, and perceived autonomy for VR design. However, research on the phenomenological differences between lucid and nonlucid dreams show mixed results [7]. We plan to test these lucid dreaming components in future phenomenological experiments.

Lucid Loop will be an open, nature scene with other interactive elements that provoke curiosity. DCNN imagery will provide a level of abstraction needed for a dream-like effect, e.g., Figure 2. The image layers themselves will range from very abstract to completely clear, mimicking levels of clarity in lucid dreaming. We do not input physiological signals directly into the DCNN yet since we first aim for high quality, artistic content that changes in real-time, and current technology does not yet allow for this. Future iterations will have physiological signals generate deep dream content in real-time.

Research Design and Implementation

This research will be conducted in two phases: validating the system components; conducting more extensive testing and an evaluation of the system's ability to increase lucid dreaming awareness.

Phase 1: Test and Validate Components.

First, we will measure physiological signals from brain waves, heart rate, and respiration to validate participants' experience of lucid awareness. We will collect data from participants wearing *Muse 2* with a VR HMD over top. We will measure a baseline EEG reading using the Klimesch Technique, where we measure each band during two minutes of eyes open and one minute of eyes closed [22]. This provides a measure of individual frequency for each band. We will collect and record data with *Muse Direct*, a visualization and recording tool for *Muse 2*.

Phase 2: Evaluation of System. We will use a mixed methods approach by triangulating data to evaluate *Lucid Loop*. Physiologically, we will measure outputs from brain waves, heart rate, and respiration. We will look at self-reported responses from both validated questionnaires and semi-structured interviews based on cued-recall debrief—a method that allows the participant to fully experience the system without disruption and avoids memory bias by showing the participant a first-person perspective recording of their experience [18].

ACKNOWLEDGEMENTS

We gratefully acknowledge funding from the Social Sciences and Humanities Research Council of Canada.

Biofeedback Mapping

The participant experiences real-time biofeedback in the form of creative visuals and audio that are mapped to data from *Muse 2*, a wearable headband comprised of five frontal EEG electrodes including one baseline; one photoplethysmogram (PPG); one gyroscope; one accelerometer. Heart rate is calculated from PPG, and respiration from a combination of PPG and gyroscope. Brain waves (μV) are read from EEG electrodes, where a Fast Fourier Transformation then computes the power spectral density of each frequency on each channel. We take the log of the sum of the power spectral density of EEG data over a frequency range (i.e., γ , β , α , θ , and δ) to calculate the absolute power bands. The mean γ , β and θ power levels of all EEG electrodes are then normalized to a score between 0 and 1. The score is 0 if \leq 20th percentile of the distribution of band powers and 1 if \geq 80th percentile. The higher the score, the greater the change in band power. Thus, if a participant increases their γ , β and θ scores, this indicates that lucidity is also increased and the image and audio will become clearer. Likewise, when γ , β and θ scores decrease, then lucidity decreases and the image and audio will become more abstract. Increased heart rate and respiration will also contribute to a clearer or more lucid image, but to a lesser extent since these physiological responses are innervated by both sympathetic and parasympathetic nervous systems so the meaning of their responses is less evident.

CONCLUSIONS AND IMPLICATIONS

We propose a novel VR deep learning biofeedback system for lucid dreaming awareness. Components of *Lucid Loop* have already been developed, but the combination of them is what makes this system unique. Moreover, an embodied experience of practicing lucid dreaming awareness without having to actually be asleep is also new. *Lucid Loop* has the potential to provide a powerful new tool to complement the increased interest of research into lucid dreaming and its practices, whose benefits contribute to well-being. *Lucid Loop* uses direct feedback to playfully support awareness of one's state, ultimately helping to self-regulate one's state and enable more frequent or sustained lucid dreams.

REFERENCES

- [1] Li Alin. 2018. V.DREAM. <http://www.lialin.net/>
- [2] Judith Amores, Xavier Benavides, and Pattie Maes. 2016. PsychicVR: Increasing mindfulness by using virtual reality and brain computer interfaces. In *Proceedings of the 2016 CHI Conference Extended Abstracts on Human Factors in Computing Systems*. ACM, 2–2.
- [3] Robin Arnott. 2017. Soundself. <https://soundselfgame.com/>
- [4] Steve DiPaola. 2007. Knowledge based approach to modeling portrait painting methodology. In *EVA*.
- [5] Steve DiPaola and Graeme McCaig. 2016. Using Artificial Intelligence Techniques to Emulate the Creativity of a Portrait Painter. In *EVA*.
- [6] Ellipsis Entertainment. 2018. Somnai. <https://www.dotdot.london/>

- [7] Jayne Gackenbach and Stephen LaBerge. 2012. *Conscious mind, sleeping brain: Perspectives on lucid dreaming*. Springer Science & Business Media.
- [8] Andrea Gaggioli, Giuseppe Riva, Dorian Peters, and Rafael A Calvo. 2017. Positive technology, computing, and design: shaping a future in which technology promotes psychological well-being. In *Emotions and Affect in Human Factors and Human-Computer Interaction*. Elsevier, 477–502.
- [9] Andrew Holecek. 2016. *Dream yoga: illuminating your life through lucid dreaming and the Tibetan yogas of sleep*. Sounds True.
- [10] Brigitte Holzinger, Stephen LaBerge, and Lynne Levitan. 2006. Psychophysiological correlates of lucid dreaming. *Dreaming* 16, 2 (2006), 88.
- [11] Alexandra Kitson, Mirjana Prpa, and Bernhard E Riecke. 2018. Immersive interactive technologies for positive change: a scoping review and design considerations. *Frontiers in psychology* 9 (2018).
- [12] Alexandra Kitson, Thecla Schiphorst, and Bernhard E Riecke. 2018. Are You Dreaming?: A Phenomenological Study on Understanding Lucid Dreams as a Tool for Introspection in Virtual Reality. In *Proceedings of the 2018 CHI Conference on Human Factors in Computing Systems*. ACM, 343.
- [13] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. 2012. Imagenet classification with deep convolutional neural networks. In *Advances in neural information processing systems*. 1097–1105.
- [14] Stephen LaBerge. 1990. Lucid dreaming: Psychophysiological studies of consciousness during REM sleep. *Sleep and cognition* 1990 (1990), 109–126.
- [15] Stephen LaBerge, Lynne Levitan, and William C Dement. 1986. Lucid dreaming: Physiological correlates of consciousness during REM sleep. *The journal of mind and behavior* (1986), 251–258.
- [16] Graeme McCaig, Steve DiPaola, and Liane Gabora. 2016. Deep convolutional networks as models of generalization and blending within visual creativity. *arXiv preprint arXiv:1610.02478* (2016).
- [17] Alexander Mordvintsev, Christopher Olah, and Mike Tyka. 2015. Inceptionism: Going deeper into neural networks. (2015).
- [18] Mary M Omodei and JIM McLennan. 1994. Studying complex decision making in natural settings: using a head-mounted video camera to study competitive orienteering. *Perceptual and motor skills* 79, 3 (1994), 1411–1425.
- [19] Robert F Potter and Paul Bolls. 2012. *Psychophysiological measurement and meaning: Cognitive and emotional processing of media*. Routledge.
- [20] Mirjana Prpa, Kıvanç Tatar, Bernhard E Riecke, and Philippe Pasquier. 2017. The Pulse Breath Water System: Exploring Breathing as an Embodied Interaction for Enhancing the Affective Potential of Virtual Reality. In *International Conference on Virtual, Augmented and Mixed Reality*. Springer, 153–172.
- [21] Melanie Schädlich and Daniel Erlacher. 2012. *Applications of lucid dreams: An online study*. Citeseer.
- [22] Richard M Shiffrin and Walter Schneider. 1977. Controlled and automatic human information processing: II. Perceptual learning, automatic attending and a general theory. *Psychological review* 84, 2 (1977), 127.
- [23] Tadas Stumbrys, Daniel Erlacher, Miriam Johnson, and Michael Schredl. 2014. The phenomenology of lucid dreaming: an online survey. *The American Journal of Psychology* 127, 2 (2014), 191–204.
- [24] Keisuke Suzuki, Warrick Roseboom, David J Schwartzman, and Anil K Seth. 2017. A deep-dream virtual reality platform for studying altered perceptual phenomenology. *Scientific Reports* 7, 1 (2017), 15982.
- [25] Ursula Voss, Romain Holzmann, Allan Hobson, Walter Paulus, Judith Koppehele-Gossel, Ansgar Klimke, and Michael A Nitsche. 2014. Induction of self awareness in dreams through frontal low current stimulation of gamma activity. *Nature neuroscience* 17, 6 (2014), 810.
- [26] Ursula Voss, Romain Holzmann, Inka Tuin, and Allan J Hobson. 2009. Lucid dreaming: a state of consciousness with features of both waking and non-lucid dreaming. *Sleep* 32, 9 (2009), 1191–1200.